

Liberty Pumps®

50Hz

FL150-E Series

**Submersible
Effluent Pump**

1.1 kW

**1.5" and 2"
NPT Discharge**

Features:

- Heavy cast iron housing and volute
- Oil-filled motor
- Permanently lubricated upper and lower ball bearings
- Stainless steel rotor shaft
- Semi-open cast iron impeller
- 1.9 cm solids-handling design
- Dual shaft seals
- 10 m power cord
- 2" NPT Discharge with 1.5" cast iron flange provided



3
Year Warranty



**Dual sized discharge
1-1/2" or 2"**



innovate. evolve.



FL150-E Submersible Effluent Pump

Specifications

Feature	FL152M-3E	FL153M-3E	FL154M-3E
Motor	Submersible	Submersible	Submersible
kW	1.1	1.1	1.1
Phase	1	3	3
Voltage	230	230	400
Hz	50	50	50
RPM	2875	2875	2875
Amps	10.2	13.3	4.9
Locked Rotor Amps	48	68	32
Max. Fluid Temp. (Continuous)	40° C	40° C	40° C
Motor Insulation	Class B	Class B	Class B
Thermally Protected	Yes (internal)	No (requires panel)	No (requires panel)
Dual Discharge Size	1.5"/2" NPT	1.5"/2" NPT	1.5"/2" NPT
Solids-handling	1.9 cm	1.9 cm	1.9 cm
Power Cord	H07RN-F 700V	H07RN-F 700V	H07RN-F 700
Cord Length	10 m	10 m	10 m
Weight kg	45	45	45
Certifications	CE	CE	CE
<i>CISPR 14 for all models</i>			



All Models IP68 rated.

Materials

Handle	Stainless Steel with rubber over-mold grip
Oil	ISO VG10
Motor Housing	Cast iron – class 25
Volute Housing	Cast iron – class 25
Rotor Shaft	300-series stainless steel
Seal Upper	Silicon carbide/silicon carbide
Seal Lower	*Viton double-lip
Impeller	Cast iron, semi-open
Fasteners	300-series stainless steel
Lift out Clasp	300-series stainless steel
Exterior Coating	Powder coated – all cast iron parts

*Viton is a Registered trade mark of Dupont Dow Elastomers LLC.

Performance Curve 50 Hz



Specifications subject to change without notice.