

3

Solids Handling

| Code | Description |
|------|-------------|
| 3    | 3"          |

X L V

Pump Type

| Code | Description                  |
|------|------------------------------|
| XLV  | Vortex<br>Hazardous Location |

1 0

Horsepower

| Code | Description |
|------|-------------|
| 10   | 10 hp       |

Voltage

| Code | Description                     |
|------|---------------------------------|
| 3    | 200/230V 3Ø-208V or 240V system |
| 4    | 460V 3Ø-480V system             |
| 5    | 575V 3Ø-600V system             |

A

Frequency Hz

| Code | Description |
|------|-------------|
| A    | 60 Hz       |

Impeller Size

| Code | Description |
|------|-------------|
| 0700 | 7.0"        |
| 0725 | 7.25        |
| 0750 | 7.5"        |
| 0775 | 7.75"       |
| 0800 | 8.0"        |
| 0825 | 8.25"       |
| 0850 | 8.5"        |

C

Impeller Material

| Code | Description |
|------|-------------|
| C    | Cast Iron   |

2

Seal Config

| Code | Description |
|------|-------------|
| 2    | Dual Seal   |

Lower Seal

| Code | Description                                |
|------|--------------------------------------------|
| S    | Silicon Carbide on<br>Silicon Carbide      |
| T    | Tungsten Carbide<br>on Tungsten<br>Carbide |

E C

Discharge

| Code | Description                                |
|------|--------------------------------------------|
| EC   | Horizontal, 4" 150# ANSI<br>(DIN 100-PN10) |

Cord Type

| Code | Description                 |
|------|-----------------------------|
| A    | Permanent                   |
| B    | Heavy-duty<br>Quick-connect |

Cord Length

| Code | Description |
|------|-------------|
| -3   | 35'         |
| -5   | 50'         |
| -1   | 100'        |

Denotes Standard Construction

Specifications are subject to change without notice.