



Engineered**Products**

NEMA 1



NEMA 4X



SX-Series

Simplex Pump Control Panels

For reliable control of a single pump in residential or commercial installations. Common applications include sump basins, effluent, or sewage pump chambers and lift stations.

- Across-the-line magnetic contactor
- Hand-Off-Auto switches
- Terminal block for easy wiring
- Circuit breaker
- Green pump run indicator light (internal)
- Red alarm indicator light/audible alarm
- Auxiliary Contacts
- Alarm silence and test switches
- 120/208/240V operation on single phase
- 208/240/480/575V operation on three phase

Other Available Options:

- Alarm bell
- Redundant off
- Cycle counter
- Dead front
- Main disconnect
- Flasher
- Manual alarm reset
- Power on light
- Lockable latch
- Overload protection
- Alternate beacon color
- High and low level indicators
- Seal fail indicator
- Anti-condensation heater
- Pilot breaker
- Overload reset, thru-door
- Beacon guard
- Thermal cutout
- Elapsed time meter
- Delay timer
- Lightning arrestor
- GFI convenience receptacle
- Start/Run Capacitors

Proudly engineered
and built in the USA



SX-Series Simplex Pump Controls

Model Specifications

Model	Volts	Phase	Full Load AMPS (Must match pump)	Enclosure
Single Phase				
SXL21=3	120/208/240	1	0 - 14.9 amps	NEMA 1
SXL24=3	120/208/240	1	0 - 14.9 amps	NEMA 4X
SXH21=3	120/208/240	1	15 - 20 amps	NEMA 1
SXH24=3	120/208/240	1	15 - 20 amps	NEMA 4X
SXK24=3	120/208/240	1	20 - 30 amps	NEMA 4X
SX24LC1=3**	120/208/240	1	0 - 14.9 amps	NEMA 4X
SX24HC1=3**	120/208/240	1	15 - 20 amps	NEMA 4X
SX24KC1=3**	120/208/240	1	20 - 30 amps	NEMA 4X
SXH24HS1=3**	120/208/240	1	15 - 20 amps	NEMA 4X
Three Phase*				
SX34=3-141	208/240/480	3	2.5 - 4.0 amps	NEMA 4X
SX34=3-171	208/240/480	3	4.0 - 6.3 amps	NEMA 4X
SX34=3-191	208/240/480	3	6 - 10 amps	NEMA 4X
SX34=3-511	208/240/480	3	9 - 14 amps	NEMA 4X
SX34=3-611	208/240/480	3	13 - 18 amps	NEMA 4X
SX34=3-621	208/240/480	3	17 - 23 amps	NEMA 4X
SX54=3-151	575	3	2.5 - 4.0 amps	NEMA 4X
SX54=3-405	575	3	6 - 10 amps	NEMA 4X

* Three phase panels come equipped with thermal overload protection that must be properly sized to the pump's full-load run amps. Multi-tap transformer (208/240/480VAC primary) provides 120V control voltage. Motor protective switch provides adjustable overload, branch circuit protection and pump disconnect. Please consult factory for proper panel selection. (35' and 50' cord length options available. Add "-3" or "-5" suffix to model number. Example: SXL21=3-5 for 50' cords.)

**SX24LC1=3, SX24HC1=3, SX24KC1=3, and SXH24HS1=3 require capacitor kit. Consult pump literature for appropriate panel and capacitor selection.

SX-Series Features

Enclosure: 8" x 8" x 4"; NEMA 4X – ultraviolet stabilized thermoplastic for outdoor; NEMA 1 – metal for indoor use. Certain options may increase enclosure size. (Three phase panels measure 12" x 10" x 6".)

Magnetic Motor Contactor

Hand-Off-Auto Switches: Offers manual operation of pump (on circuit board).

Green Pump Run Indicators: On circuit board.

Control On/Off Switch: Mounted on circuit board.

Float Switch Terminal Block: On circuit board.

Control and Alarm Fuses: On circuit board.

Control and Alarm Power Indicators: On circuit board.

Circuit Breaker: Single phase panels include circuit breaker to provide pump disconnect and branch circuit protection. Three phase breakers sized to application and provide additional overload protection for the pump.

Pump Input Power and Pump

Connection Terminal Block

Ground Lug

Auxiliary Contacts

Alarm Package: NEMA 4X = red beacon and horn (83 to 85 dB), exterior test/normal/silence switch. NEMA 1 = door mounted red indicator and buzzer mounted internally (83 to 85 dB), exterior test/normal/silence switch.

Switch Specifications

All standard simplex panels include 3 pilot-duty float switches for Off, On, and Alarm. 20' cord standard. Optional lengths available. External weights or pipe clamp mounts required.

Liberty can customize a panel to your specific pump needs. Please contact us for available options and ordering information. 800-543-2550

Cable: Flexible 18 gauge, 2 conductor

Electrical: 5 amp, 120/230VAC, 50/60Hz

Float: High impact PVC

140 degrees F. maximum fluid temperature

Weight:

NEMA 1 Panels: 24 lbs. (approx.)

NEMA 4X Panels: 19 lbs. (approx.)



Dual safety certification for
the United States and Canada.