

LSG300-SERIES

Sewage Grinder Pump

Liberty Pumps®

A Family and Employee Owned Company

commercial**series**

3 hp

**2", 2-1/2" & 3" ANSI® Horizontal
Discharge with 2" NPT**

**2"/3" NPT Vertical Discharge
Models Available**


Features

- Cast iron construction with durable powder coat finish
- Stainless steel hardware
- Buna-N O-ring seals
- Quick-connect cords in 35' & 50' lengths
- V-Slice® Cutter Technology
- Dual seal with seal leak detection
- MidTherm™ Cooling provides more efficient motor cooling


NEW!

Combo Volute

One pump, multiple discharge options



Horizontal discharge models feature ANSI® 150# 2"-3" and a 2" NPT



Vertical discharge models feature a 2" threaded elbow with a 3" threaded flange



Patent: See
LibertyPumps.com/en-us/patents

***Proudly made in the USA
with US & global components***

innovate. evolve.

LSG300-Series

Impeller

Balanced stainless steel

Finish

Powder coat

Max Fluid Temperature

104°F (40°C) Continuous duty

Motor

Oil-filled, Class F insulation,
Inverter duty rated

Power Cord Type

SOOW, Quick-connect 35' or 50'
length options

Motor Housing

Class 30 cast iron

Volute

Class 30 cast iron

Shaft

Stainless steel

Mechanical Shaft Seals

Dual seal arrangement

- Lower (primary) silicon carbide/
silicon carbide
- Upper (secondary) carbon/ceramic

Bearings


- Upper bearings single row deep groove
- Lower bearings double row angular contact

Warranty

18 Months from the date of installation or
24 months from the date of manufacture
*See Liberty Pumps Limited Warranty - Wholesale
Commercial Series*

Performance Curve

60 Hz, 3450 RPM





V-Slice® Cutter Technology




Patent: See
LibertyPumps.com/en-us/patents




Dimensional Data - ANSI® Horizontal Discharge



**Optional 4" ANSI®
Discharge Kit K002016
[sold separately]**



2", 2.5" & 3" 150# ANSI
(DIN 50-PN10, DIN 65-PN10, AND DIN 80-PN6)
WITH 2" NPT



Models - ANSI® Horizontal Discharge

MODEL	HP	VOLTS	PHASE	AMPS	CORD LENGTH	DISCHARGE	WEIGHT in LBS
LSGV302M-3	3	230**	1	19	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGV303M-3	3	200/230*	3	13/11.8	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGV304M-3	3	460	3	5.8	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGV305M-3	3	575	3	5	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGH302M-3	3	230**	1	19	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGH303M-3	3	200/230*	3	13/11.8	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGH304M-3	3	460	3	5.8	35'	2", 2.5" & 3" ANSI Horizontal	270
LSGH305M-3	3	575	3	5	35'	2", 2.5" & 3" ANSI Horizontal	270



For 50' cord option, add "-5" suffix to model number. Example: LSGV302M-5 *System voltages: 208 and 240 volts with utilization voltages: 200 and 230 volts

**1-phase models require an externally mounted start circuit for operation. Start circuit kits are available and sold separately.

Refer to installation manual for circuit details.

LSG300-Series

Dimensional Data - Vertical Discharge



Models - Vertical Discharge

MODEL	HP	VOLTS	PHASE	AMPS	CORD LENGTH	DISCHARGE	WEIGHT in LBS
LSGV302MV-3	3	230**	1	19	35'	2" & 3" NPT Vertical	270
LSGV303MV-3	3	200/230*	3	13/11.8	35'	2" & 3" NPT Vertical	270
LSGV304MV-3	3	460	3	5.8	35'	2" & 3" NPT Vertical	270
LSGV305MV-3	3	575	3	5	35'	2" & 3" NPT Vertical	270
LSGH302MV-3	3	230**	1	19	35'	2" & 3" NPT Vertical	270
LSGH303MV-3	3	200/230*	3	13/11.8	35'	2" & 3" NPT Vertical	270
LSGH304MV-3	3	460	3	5.8	35'	2" & 3" NPT Vertical	270
LSGH305MV-3	3	575	3	5	35'	2" & 3" NPT Vertical	270

For 50' cord option, add "-5" suffix to model number. Example: LSGV302MV-5 *System voltages: 208 and 240 volts with utilization voltages: 200 and 230 volts

**1-phase models require an externally mounted start circuit for operation. Start circuit kits are available and sold separately.

Refer to installation manual for circuit details.