

STANDARD ALARMS

For Sump, Sewage and Effluent

Liberty Pumps®

A Family and Employee Owned Company

ALM-Series

- Indoor rated
- 115V Operation with 9-volt battery backup
- 86 Decibel horn
- Red LED alarm ring
- Green power "ON" light
- Auxiliary contacts
- Automatic alarm reset
- Alarm Test / Silence buttons
- 9-volt battery included

See **ALM-EYE Series** literature for Wi-Fi connected models

Patent: See
LibertyPumps.com/en-us/patents



Super bright
LED alarm ring

Models

- ALM-2-1** Narrow angle float switch, 10' cord
ALM-2 Narrow angle float switch, 20' cord
ALM-P1 Compact snap-on float switch, 10' cord
ALM-PK Puddle sensor, 50' cord



**Narrow Angle
Float Switch**
(Sewage/Effluent
application)



**Compact Snap-on
Float Switch**
Fits 1-1/4" or 1-1/2" pipe
(Sump application)



Puddle Sensor
(For floor level sensing)



ALM-2W & ALM-230W

Indoor/Outdoor
ALM-2W - 115V
ALM-230W - 230V

- Meets Enclosure Type 3R Standards
- 115V Operation, direct wire
- Thermoplastic enclosure
- Red alarm beacon
- 82 Decibel horn
- Alarm Test / Silence switch
- 20' Float switch cord
- Includes auxiliary contacts
- Easy field wiring with removable cover



ALM-3W

Commercial Outdoor

- NEMA 4X rated
- Commercial-duty enclosure
- 115V Operation, direct wire with 9-volt battery backup
- Flashing red alarm LEDs
- 95 Decibel horn
- Alarm "Test / ON / Silence" switch
- 20' Float switch cord
- Includes auxiliary contacts
- Battery not included

